

Yealink

SIP-T33G



Yealink SIP-T33G is an entry-level, high performance SIP phone, bringing a comfortable and clear visual experience to its users. With an extra-large, color, backlit display and flexible features, it maximizes productivity in both small and large office environments.

KEY FEATURES

- Yealink HD Voice
- 2.4" 320 x 240-pixel color display with back-light
- Dual-port Gigabit Ethernet
- PoE support
- Unified Firmware
- Color Screen
- Elegant Industrial Design

SIP-T33G PHONE PRODUCT SPECIFICATIONS

Audio Features

- HD voice: HD handset, HD speaker
- Smart Noise Filtering
- Wideband codec: G.722
- Narrowband codec: G.711(A/μ), G.729, G.729A,
- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJB, AGCE

Phone Features

- 4 VoIP accounts
- Call hold, mute, DND
- One-touch speed dial, hotline
- Call forward, call waiting, call transfer
- Group listening, SMS, emergency call
- Redial, call return, auto answer
- Local 5-way conferencing
- Ring tone selection/import/delete
- Set date time manually or automatically
- Dial plan
- XML Browser, action URL/URI
- Integrated screenshots
- RTCP-XR, VQ-RTCPXR
- Enhanced DSS Key

Directory

- Local phonebook up to 1000 entries
- XML/LDAP remote phonebook
- Smart dialing
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded

IP-PBX Features

- Busy Lamp Field (BLF), Bridged Line Appearance (BLA)
- Anonymous call, anonymous call rejection
- Voice mail
- Flexible seating
- Call park, call pickup
- Centralized call recording
- Visual voice mail

Display and Indicator

- 2.4" 320 x 240-pixel color display with backlight
- 16 bit depth color
- LED for call and message waiting indication
- Dual-color (red or green) illuminated LEDs for line status information
- Wallpaper
- Intuitive user interface with icons and soft keys
- Multilingual user interface
- Caller ID with name and number
- Screensaver
- Power saving

Feature keys

- 4 line keys with LED
- 4 line keys can be programmed up to 12 paper-less DSS keys (4-page view)
- 5 features keys: message, headset, redial, mute, hands-free speakerphone
- 6 navigation keys
- Volume control keys

Interface

- Dual-port Gigabit Ethernet
- Power over Ethernet (IEEE 802.3af), class 2
- 1 x RJ9 (4P4C) handset port
- 1 x RJ9 (4P4C) headset port

Other Physical Features

- Color: Classic Grey
- Wall mountable
- External Yealink AC adapter
AC 100~240V input and DC 5V/600mA output
- Power consumption (PSU): 2-3W
- Power consumption (PoE): 3.5-5W
- Dimension (W*D*H*T):
212mm*186mm*146mm*42mm
- Operating humidity: 10~95%
- Operating temperature: -10~50°C (+14~122°F)

Management

- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Zero-sp-touch, TR-069
- Phone lock for personal privacy protection
- Reset to factory, reboot
- Package tracing export, system log

Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- Call server redundancy supported
- NAT traversal: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV (RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- SRTP for voice
- Transport Layer Security (TLS)
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication
- OpenVPN, IEEE802.1X
- IPv6
- LLDP/CDP/DHCP VLAN
- ICE

Package Features

- Package content:
 - Yealink SIP-T33G IP phone
 - Handset with handset cord
 - Ethernet Cable (1.5m CAT5E UTP Cable)
 - Stand
 - Quick Start Guide
 - Power Adapter (Optional)
- Qty/CTN: 10 PCS
- N.W/CTN: 9.56 kg
- G.W/CTN: 10.52 kg
- Giftbox size: 238 mm*210 mm*103 mm
- Carton Meas: 535 mm*443 mm*250 mm

QUESTIONS? CONTACT US TODAY!

Function4

281-565-1100

info@function-4.com
<https://www.function-4.com/>